



## **FEATURES**

- 15.6" IPS LCD Screen (1920 x 1080 Resolution)
- Powerful ARM Processor (Optional Intel CPU)
- Android 11 OS (Optional Window 11)
- Anti-corrosion 316L Stainless Steel Chassis
- IP65 Water & Dust Protection
- 1 Emergency Stop Button
- 3 Programmable Buttons
- Sunlight–Readable Display
- Capacitive Touch Screen (Support Glove or Wet Touch)

The HMI-1500 is the ultimate rugged Control Panel, meticulously engineered for the harshest industrial environments. Its corrosion-resistant 316L stainless steel body ensures long-lasting durability, even in highly corrosive settings like car washes or food processing industries. With a sunlight-readable 15.6" IPS LCD display and capacitive 10-point multi-touch, it offers crystal-clear visuals and precise interaction, no matter if you are indoor or out in challenging conditions. Powered by Quad Cortex-A53 + Quad Cortex-A72 processor and running on Android 14 (optional Intel N200 CPU and Window OS), this device delivers seamless performance. Enhanced with an Emergency Stop Button and programmable buttons, the HMI-1500 is a reliable and adaptable command center designed to maximize safety and efficiency in demanding applications.

## **SPECIFICATIONS**

RUGGEDNESS		POWER	
IP Rating	IP65	AC Adapter	Input AC 100-240V, Output DC 12V 3A
<b>ESD Protection</b> ±8kV (Air), ±4kV (Touch)			
EMC Test	Follows FCC	I/O INTERFACE	
SYSTEM		– Audio	Optional
		Camera	Optional
Processor	Quad Cortex-A53 + Quad Cortex-A72, 2.2GHz	Ports	1 x 1000M Ethernet
	Optional: Intel CPU N200 CPU		1 x USB 3.0
GPU	Mali-G52 MC3 MP4 GPU		1 x RS485
Memory	4GB LPDDR4		1 x DC in
	Optional: 8GB	Buttons	Power On/Off Button, Support 10s Hard Reset
Storage	32 GB		3 x Programmable Buttons
	Optional: 64GB / 128GB		1 x Emergency Stop Button
OS	Android 14		
	Optional: Linux or Window 11	MECHANICAL	
		– Chassis	Front Chassis: 316L Stainless Steel
DISPLAY			Rear Chassis: 316L Stainless Steel
Screen Size	15.6" IPS LCD		Mounting: 100mm x 100mm VESA Mount
Resolution	1920 x 1080	Dimensions	417 x 288.5 x 46mm
Brightness	800 nits		
Touch Screen	Capacitive 10-Point Multi-Touch	ENVIRONMENTAL	
		_ Temperature:	
COMMUNICATIONS		- Operation	0°C to 50°C
Wi-Fi	WiFi 6 802.11 a/b/g/n/ac/ax	- Storage	-20°C to 60°C
Bluetooth	Bluetooth V4.2	Humidity	10% to 90% Non-condensing
		REGULATORY	
		REGULATORY	

www.estonetech.com sales@estonetech.com U.S.-Headquarters 2900 Carskaddon Ave, Toledo, OH 43606 U.S.-West Coast 21015 Commerce Pointe Dr, Walput, CA 91789

Certification

**Europe** Baltesakker 17-A, 5625 TC, Eindhoven, The Netherlands

FCC, RoHS Compliant

**Japan** 101-0021, 4F Kairaku Shinsuehiro Bld. 6-5-12, Sodokanda, Chiyoda-Ku, Tokyo

# 15.6" STAINLESS CONTROL PANEL | HMI-1500



## **DIMENSIONS AND SYSTEM LAYOUT**











## **MARKET & APPLICATIONS**

- Food & Beverage Manufacturing Industry Automatic Car Wash Systems Outdoor Industrial Operations Pharmaceutical and Chemical Manufacturing Agricultural and Farming Equipment
- **Oil and Gas Industry**



www.estonetech.com sales@estonetech.com **U.S.-Headquarters** 2900 Carskaddon Ave, Toledo, OH 43606 **U.S.–West Coast** 1015 Commerce Pointe Dr, Walnut, CA 91789 **Europe** Baltesakker 17-A, 5625 TC, Eindhoven, The Netherlands **Japan** 101-0021, 4F Kairaku Shinsuehiro Bld. 6-5-12, Sodokanda, Chiyoda-Ku, Tokyo